

CCTV Surveillance Power Supply PS64-2

Description & Features

PS64-2 is a highly reliable power supply with 9 output channels. Its main output is 12 - 14VDC at 10A. Used for CCTV surveillance systems.



SPECIFICATION

| | | | |
|-------------------------|--------------------|--|---------------------|
| INPUT | Voltage Range | 100 - 240VAC | |
| | Frequency Range | 50 - 60Hz | |
| | Efficiency (Typ.) | >85% | |
| OUTPUT | Voltage | 12 - 14V adjustable | |
| | Rated Current | 10A | |
| | Rated Power (Max.) | 70W (under 14V output voltage) | |
| | Ripple & Noise | <100mVp-p | |
| | Line Regulation | ±2% | |
| | Load Regulation | ±2% | |
| | Output Channel | 9 channels | |
| PROTECTION | Input Fuse | 5A / 250VAC | |
| | Output Fuse | 1.1 per channel | |
| | Overload | 11A ±5%, Hiccup mode, recovers automatically after fault condition is removed. | |
| ENVIRONMENT | Temperature | Working: -20 - 50°C | Storage: -30 - 80°C |
| | Humidity | Working: 20 - 80%RH | Storage: 10 - 90%RH |
| SAFETY & EMC | EMC Standards | Complies with EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3 | |
| | LVD Standards | Complies with EN 60950-1 | |
| Metal Box | 203 x 203 x 54 mm | | |